



HYDRAULIC OIL HM 46

Product Description:

HYDRAULIC OIL HM 46 is a universal mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

HYDRAULIC OIL HM 46 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Excellent stability against oxidation.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.

HYDRAULIC OIL HM 46 exceeds the following performance criteria.:

AFNOR NF E 48-603
DIN 51524/2 HLP

ISO 11158 HM

ISO 6743-4 HM



Property	Unit	Test Method	Typical Value
ISO Grade		ISO 3448	46
Density@15°C	kg/m ³	ASTM D4052	876
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	45.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.8
Viscosity Index		ASTM D2270	104
Flash Point COC	°C	ASTM D92	>180
Pour Point	°C	ASTM D97	-33
Demulsibility @54°C	min	ASTM D1401	10

Product Nr: 43540

Date Superseded: 21-10-2011

Date Issued: 20-12-2019

Revision nr: 03